



MODEL MTO2V 8030

Proper to contemporarily cut both in horizontal sense that vertical with a speed of cut from 0 ÷ 25 m/min.

Unlike the model MTOV the vertical cut is predisposed to the left for the assemblage of the disk. Solution that allows to use the machine for the only Vertical tracings (in case of lack of the model MTV.)

Slide on binary type T 70 / U 80

Total power Kw63,5

Depth of Vertical max300mm.

Depth of Horizontal cut max250mm

Vertical disk f 850mm.

Horizontal disk f 650mm.

Recommended generator KVA 100

ELECTRIC MOTORS

- Vertical cut kw 30
Type IP 55 Class F η 0, 87÷ 0,92V 380 50 Hz B3
- Horizontal cut Kw 30
Type IP 55 Class F η 0, 87÷ 0,92V 38050 Hz B3
- Advancement Kw2
Type IP 55 Class F η 0, 80÷ 0,92V 380 50 Hz B5
- I install hydraulic Kw1,5
Type IP 55 Class F η 0, 80÷ 0,92V 380 50 Hz B5

With commands of driving to low tension as foreseen by the law
Opportunely proportionate and pulsating of march / single arrest for every motor.

SAFETY

The machine is provided of electric devices of block that make her/it sure and of acoustic and bright device that warns that the cars it is in movement. And' provided of protections on all the mechanical organs in movement and protection on the disks up to maximally possible.

I INSTALL HYDRAULIC

Pomp to gears. distributor to3 elements

Brought 10 litri/1'

Pressure 100 ÷ 150 bar

Ability reservoir 50Lt.

ADVANCEMENT OF CUT

Hydraulic to varying course

independent operated through lever

inversion of march with point of madman

speed max. 50 @m/min. 4 to empty

4 wheels engines

LOOM

It structures in steel on purpose studied for a' tall resistance, elettrosaldato. Articulation vertical cut, to hydraulic command through hydraulic martinetto to double effect; Translation cart for Horizontal loom through martinetto to double effect And it flows on pads and adjustable guides to annul the game of usury. Driving Horizontal cut through hydraulic martinetto to double effect integrated in a system of levers.

MEASURE AND MASS

Width 1800 mm. ~

Lenght 2200 mm. ~

Height 1700 mm. ~

Weigth 2500 Kg. ~

Gives technical and characteristics can suffer variations



40 ANNI DI ESPERIENZA NEL SETTORE DELLE MACCHINE CAVATUFO E CAVAPIETRA

Magisa ® - Macchine Cavatufo e Cavapietra - 72017 - Ostuni (BR) Italy - Zona industriale

tel. 0039 / 0831 304559 - fax. 0039 - 0831 330294

www.magisa.it - info@magisa.it

Partita iva 02044780746