



Proper to cut furrows vertical with a speed of cut from 0 ÷ 25 m/min.
Slide on binary type T 45
Total power Kw 23,5
Depth of Vertical max 300mm.
Vertical disk f850mm..
Recommended generator KVA 40

ELECTRIC MOTORS

- Vertical cut kw 22
Type IP 55 Class F η 0, 87÷ 0,92V 380 50 Hz B3
- Advancement Kw0,75
Type IP 55 Class F η 0, 75÷ 0,92V 380 50 Hz B5
- I install hydraulic Kw 0,75
Type IP 55 Class F η 0,75÷ 0,92V 380 50 Hz B5

ELECTRIC PICTURE

With commands of driving to low tension as foreseen by the law
Opportunely proportionate and pulsating of march / single arrest for every motor.

SAFETY

The machine is provided of electric devices of block that make her/it sure and of acoustic and bright device that warns that the cars it is in movement. And' provided of protections on all the mechanical organs in movement and protection on the disks up to maximally possible.

I INSTALL HYDRAULIC

Pomp to gears. distributor to2 elements
Brought 3,5litri/1'
Pressure 100 ÷ 150 bar
Ability reservoir 20Lt.

ADVANCEMENT OF CUT

Hydraulic to varying course
independent operated through lever
inversion of march with point of madman
speed max. 40 @m/min. 4 to empty
4 wheels engines

LOOM

It structures in steel on purpose studied for a' tall resistance, elettrosaldato. Articulation vertical cut, to hydraulic command through hydraulic martinetto to double effect;

MEASURE AND MASS

Width 950 mm. ~
Lenght 2350 mm. ~
Height 1800 mm. ~
Weigth 830 Kg. ~

Gives technical and characteristics can suffer variations



40 ANNI DI ESPERIENZA NEL SETTORE DELLE MACCHINE CAVATUFO E CAVAPIETRA

Magisa ® - Macchine Cavatufo e Cavapietra - 72017 - Ostuni (BR) Italy - Zona industriale

tel. 0039 / 0831 304559 - fax. 0039 - 0831 330294

www.magisa.it - info@magisa.it

Partita iva 02044780746