

## MODEL MTV 6040



Proper to cut furrows vertical with a speed of cut from 0 ÷ 25 m/min.  
Slide on binary type T 60  
Total power Kw50,2  
Depth of Vertical max 420mm.  
Vertical disk f 1200mm..  
Recommended generator KVA 85

### ELECTRIC MOTORS

- Vertical cut kw 45  
Type IP 55 Class F  $\eta$  0,87÷ 0,92V 380 50 Hz B3
- Advancement Kw 3  
Type IP 55 Class F  $\eta$  0,75÷ 0,92V 380 50 Hz B5
- I install hydraulic Kw 2,2  
Type IP 55 Class F  $\eta$  0,75÷ 0,92V 380 50 Hz B5

### ELECTRIC PICTURE

With commands of driving to low tension as foreseen by the law  
Opportunely proportionate and pulsating of march / single arrest for every motor.

### SAFETY

The machine is provided of electric devices of block that make her/it sure and of acoustic and bright device that warns that the cars it is in movement. And' provided of protections on all the mechanical organs in movement and protection on the disks up to maximally possible.

### I INSTALL HYDRAULIC

Pomp to gears. distributor to 1 elements  
Brought 8litri/1'  
Pressure 100 ÷ 150 bar  
Ability reservoir 40 Lt.

### ADVANCEMENT OF CUT

Hydraulic to varying course  
independent operated through lever  
inversion of march with point of madman  
speed max. 50 @m/min. 4 to empty  
4 wheels engines

### LOOM

It structures in steel on purpose studied for a' tall resistance, elettrosaldato. Articulation vertical cut, to hydraulic command through hydraulic martinetto to double effect;

### MEASURE AND MASS

Width 1600 mm. ~  
Lenght 2600 mm. ~  
Height 1600 mm. ~  
Weigth 2200 Kg. ~

Gives technical and characteristics can suffer variations



**40 ANNI DI ESPERIENZA NEL SETTORE DELLE MACCHINE CAVATUFO E CAVAPIETRA**

Magisa ® - Macchine Cavatufò e Cavapietra - 72017 - Ostuni (BR) Italy - Zona industriale

tel. 0039 / 0831 304559 - fax. 0039 - 0831 330294

[www.magisa.it](http://www.magisa.it) - [info@magisa.it](mailto:info@magisa.it)

Partita iva 02044780746